

## Inflatable pipe plug Lansas Ø100/200K mm

Specifications inflatable pipe plug	
Ref. Lansas	I01-0101-XX

Characteristics pipe plugs	
Max inflation pressure	2,5 bar maximum
Size usage range	100 upto 200 mm
Deflated diameter	86 mm
Deflated length	250 mm
Weight	0.8 kg
Thickness of rubber	9,5 - 10 mm
Surface plug	Surface with circular rubber profile
End plates	Aluminum
Labels	1 x Lansas brand label
Attachment cord or chain	1 x Eyebolt M6
Valve	Hose barb or quick connect coupling.
Accessories	Inflation/supply hose Chain Automotive or bicycle type valve Manometer set with T-piece, valve, manometer with glycerine with protectice rubber

Maximum back pressure* (@max inflations pressue)					
Diameter (mm)		100	125	150	200
Back pressure		2,0 Bar	1,5 bar	1,1 bar	0,5 bar

\* Attention: The values are only valid for making water tests in well cleaned concrete pipes and under normal conditions.

Technical characteristics	
Rubber type	Natural rubber (NR)
Color	Black
Hardness (Shore A)	45-55
Chemical resistance	Separate document
Temperature resistance	De -25°C à +80°C
Type of reinforcement	Aramid full body cording