

Inflatable pipe plug Lansas Ø200/500 mm

Specifications inflatable pipe plug	
Ref. Lansas	101-0201-XX

Characteristics pipe plugs	
Max inflation pressure	2,5 bar maximum
Size usage range	200 upto 500 mm
Deflated diameter	170 mm
Deflated length	725 mm
Weight	5,5 kg
Thickness of rubber	9,5 - 10 mm
Surface plug	Surface with circular rubber profile
End plates	Aluminum
Labels	1 x Lansas brand label
Attachment cord or chain	1 x Eyebolt M10
Valve	Hose barb or quick connect coupling.
Accessories	Inflation/supply hose Chain Automotive or bicycle type valve Manometer set with T-piece, valve, manometer with glycerine with protectice rubber

Maximum back pressure* (@max inflations pressue)					
Diameter (mm)	200	250	300	400	500
Back pression	2,4 Bar	2,3 Bar	2,2 bar	1,5 bar	0,4 bar

* Attention: The values are only valid for making water tests in well cleaned concrete pipes and under normal conditions.

Technical characteristics	
Rubber type	Natural rubber (NR)
Color	Black
Hardness (Shore A)	45-55
Chemical resistance	Separate document
Temperature resistance	De -25°C à +80°C
Type of reinforcement	Aramid full body cording