

## Inflatable pipe plug Lansas Ø300/600 mm

Specifications inflatable pipe plug	
Ref. Lansas	101-0300-XX

Characteristics pipe plugs	
Max inflation pressure	2,5 bar maximum
Size usage range	300 upto 600 mm
Deflated diameter	288 mm
Deflated length	715 mm
Weight	11,9 kg
Thickness of rubber	9,5 - 10 mm
Surface plug	Surface with circular rubber profile
End plates	Aluminum
Labels	1 x Lansas brand label
Attachment cord or chain	2 x Eyebolt M12
Valve	Hose barb or quick connect coupling.
Accessories	Inflation/supply hose Chain Automotive or bicycle type valve Manometer set with T-piece, valve, manometer with glycerine with protectice rubber

Maximale back pressure* (@max vuldruk)					
Diameter (mm)		300	400	500	600
Backpressure		2,4 bar	2,2 bar	2,1 bar	0,9 bar

\* Warning: The values are only valid for water tests in properly cleaned concrete pipes and under normal conditions.

Technical characteristics	
Rubber type	Natural rubber (NR)
Color	Black
Hardness (Shore A)	45-55
Chemical resistance	Separate document
Temperature resistance	De -25°C à +80°C
Type of reinforcement	Aramid full body cording