

Inflatable pipe plug Lansas Ø600/1500 mm

Specifications inflatable pipe plug	
Ref. Lansas	101-0650-XX

Characteristics pipe plugs	
Max inflation pressure	1,5 bar maximum
Size usage range	600 upto 1500 mm
Deflated diameter	570 mm
Deflated length	2180 mm
Weight	65 kg
Thickness of rubber	9,5 - 10 mm
Surface plug	Surface with circular rubber profile
End plates	Aluminum
Labels	1 x Lansas brand label
Attachment cord or chain	2 x Eyebolts M16
Valve	Hose barb or quick connect coupling.
Accessories	Inflation/supply hose Chain Automotive or bicycle type valve Manometer set with T-piece, valve, manometer with glycerine with protectice rubber

Maximum back pressure* (@max inflations pressue)					
Diameter (mm)	600	800	1000	1200	1500
Back pression	1,4 bar	1,3 bar	1,3 bar	1,1 bar	0,8 bar

* Attention: The values are only valid for making water tests in well cleaned concrete pipes and under normal conditions.

Technical characteristics	
Rubber type	Natural rubber (NR)
Color	Black
Hardness (Shore A)	45-55
Chemical resistance	Separate document
Temperature resistance	De -25°C à +80°C
Type of reinforcement	Aramid full body cording